

OpenSMTPD for the Real World

BSDCan - Mail Server Tutorial

Aaron Poffenberger

akp@hypernote.com

2019-05-15T13:00:00Z

ssl(8)

man ssl

Create Self-Signed Certificate

```
# cd $ETC/ssl  
cd /etc/ssl
```

```
# Generate RSA Certificate  
openssl genrsa -out private/server.key 2048
```

```
# Generate Certificate Signing Request (CSR)  
openssl req -new -key private/server.key \  
-out private/server.csr
```

```
# Self-sign CSR  
openssl x509 -sha256 -req -days 365 \  
-in private/server.csr \  
-signkey private/server.key \  
-out /etc/ssl/server.crt
```

smtpctl

- Documentation - smtpctl(8)

`man smtpctl`

Encrypt Password for Use with *auth* Command

```
smtptcl password
```

Logging

```
# minimal logging
```

```
smtpctl log brief
```

```
# verbose logging
```

```
smtpctl log verbose
```

Show

```
# show queue messages
smtpctl show queue
ebc3909d5c70e447|local|mda|auth|test_user@example.com|user@
user@mail.example.org|1465371066|1465716666|0|10|pending|76
"smtpd: Delivery error: 550 5.1.0 id=12326-07 - Rejected by
next-hop MTA on relaying, from MTA(smtp:[127.0.0.1]:10025)
550 Invalid recipient"
```

```
# show envelope
smtpctl show ebc3909d5c70e447
```

Trace *subsystem*

```
# (aliases/virtual/forward expansion)
```

```
smtpctl trace expand
```

```
# (matched by incoming session)
```

```
smtpctl trace rules
```

```
# (incoming sessions)
```

```
smtpctl trace smtp
```

```
# alternatively
```

```
smtpd -dvT expand -T rules -T smtp
```


smtpd

- Documentation - smtpd(8)

`man smtpd`

Check Configuration

```
smtpd -nf /etc/mail/smtpd.conf
```

Start in Foreground

with verbose logging

```
smtpd -dv
```

with some tracing

```
smtpd -dvT expand -T rules -T smtp
```

with all tracing

```
smtpd -dvT all
```